

Indiana University – Purdue University Fort Wayne
Opus: Research & Creativity at IPFW

Manufacturing & Construction Engineering
Technology and Interior Design Senior Design
Projects

School of Engineering, Technology and Computer
Science Design Projects

4-12-1982

The Shower Soaper

Nick E. Kreigh

Indiana University - Purdue University Fort Wayne

Follow this and additional works at: http://opus.ipfw.edu/etcs_seniorproj_mcetid

Opus Citation

Nick E. Kreigh (1982). The Shower Soaper.
http://opus.ipfw.edu/etcs_seniorproj_mcetid/99

This Senior Design Project is brought to you for free and open access by the School of Engineering, Technology and Computer Science Design Projects at Opus: Research & Creativity at IPFW. It has been accepted for inclusion in Manufacturing & Construction Engineering Technology and Interior Design Senior Design Projects by an authorized administrator of Opus: Research & Creativity at IPFW. For more information, please contact admin@lib.ipfw.edu.

THE SHOWER SOAPER

For

Dr. Warren W. Worthley
Department Chairman
Manufacturing Technology
Indiana-Purdue University at Fort Wayne

By: Nick E. Kreigh

ABSTRACT

Sales in the millions for pulsating shower heads prove that the public will buy a device which makes taking a shower more convenient and luxurious while saving water. Thus the inexpensive, easy-to-install Shower Soaper has a tremendous market potential.

The Shower Soaper is a device which can mix a wide range of liquids (soaps, bath oils, or shampoos) with shower water. The Soaper incorporates an easy-off valve which allows the user to save water whether or not a pulsating head is also used. The Soaper has 6 main components: a diverting valve, a jet pump, a restricting valve, a soap container, a soap nozzle, and a flow control valve. When in use, the Soaper diverts water through the jet pump, creating a partial vacuum which draws soap up and mixes it with shower water. The user can reduce the water flow to a trickle by closing the Soaper's flow control valve.

A full-scale working prototype has been built and tested. All parts of the prototype were purchased from plumbing suppliers. The tests confirmed all calculation and computer estimations. The Soaper's test program included testing with varying viscosity liquids at different water pressures, hardnesses, and temperatures and testing for ease of operation and installation. The Soaper did perform excellently on all tests. The prototype tested cost \$115; the estimated production cost is \$10.

TABLE OF CONTENTS

Letter of transmittal	i
Title page	ii
Abstract	ii
List of figures	iv
Introduction	1
Objective	3
Technical plan	4
General description	4
Criteria	10
Technical assurance	11
Design flexibility tool	13
Materials list	16
Fabrication	17
Testing	18
Objectives	18
Methodology	18
Facilities and equipment	19
Data	19
Evaluation	22
Cost	23
Summary	24
Appendix	25

LIST OF FIGURES AND TABLES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1	Shower Heads	1
2	The Shower Soaper	4
3	The Soaper's Components	5
4	Diverting Valve	6
5	Restricting Valve	7
6	Flow Control Valve	8
7	Jet Pump	8

Table

1	Restricting Valve vs. Time and Fluid Viscosity	20
2	Survey Results	21